

# LYS-WHT-38851P

### SPECIFICATION DATA SHEET

#### DECENICT DETAILS


FRODUCT DETAILS						
Manufacturer :	Jaquar	Туре:	Single piece-WC (P trap )			
Range	Lyric	Outlet	Vertical			
Colour:	White	Material:	Ceramic - Vitreous China			
Technical Details:	External diameter of outlet Ø 100 +5 -2 mm	BOM doc.NO.	JSW/12/2017/0020			
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 180 mm					

# ARTICLE NAME: SINGLE PIECE - WC







### **TECHNICAL DIMENSIONS**



TOP VIEW





ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP				
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)	Day sing Flagget design Auti agent along				
365	655	765	36.65	Box rim, Elegant design, Anti germ glaze				
ACCESSORIES PROVIDED								
UF Soft Close Seat cover				LYS-WHT-38101UF				
Floor fixing screw				ZPS-SNS-FB01				

CARE AND CLEANING GUIDELINES

\* Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.

- ★ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ★ Carefully inspect the new product for damage before installation.
- $\bigstar$  Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- $\bigstar$  Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- $\bigstar$  Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

## CERTIFICATION

# Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1, BS EN 14124:2004

All technical dimensions are in accordance to British standards, Bureau of Indian Standards

PACKAGING DETAIL				LOADING PALLET DETAIL				
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	no of pieces on palle	et
670	375	765	41.50	1140	1140	2285	12	
	J <sub>P</sub>							
Prepared By		Controlled By		Verified By		Approved By		
Designer		Quality control		Product Manager		Sanitaryware Head		
Date								
Revision/Version 1			Plotter Updated on	Month	10-Jul	Year 2018		