



|  |   |
|--|---|
| <b>Product Code</b>                      | KUP-CHR-35011BPMCLW   |
| <b>Description</b>                       | Single Lever Basin Mixer without Popup Waste, with 375mm Long Braided Hoses & click clack waste (ALD-729)   |
| <b>Connection Size</b>                   | Braided hoses, 1/2" FIP (WRAS Approved)<br>Withstand pressure of 10 Bar   |
| <b>Flow Rate</b>                         | 13.09 LPM @ 3 bar   |
| <b>Flow regulator</b>                    | By using flow regulators (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GD-3.8 LPM @ 3.0 Bar pressure) one can regulate the flow rate.   |
| <b>Recommended Water Pressure</b>        | 0.5 Bar - 5 Bar   |
| <b>Brass Specification in Percentage</b> | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Sheets as per IS:410-1977</b><br/>Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> |
| <b>Cartridge Specification</b>           | NSF-61 Approved Cartridge with Temperature Limiter<br>Cartridge with Brass Spindle<br>Life Cycle EN 817: 70,000 cycles (Standard)<br>- 0.21 Million Cycles as per EN 817*<br>- 1.05 Million Cycles (ON/OFF)*  |
| <b>Accessories incl.</b>                 | Click Clack Basin Waste   |
| <b>Water Tightness</b>                   | 16 bar (Pass)   |
| <b>Pressure Resistance</b>               | 25 bar (Pass)   |
| <b>Finish</b>                            | Plating: Nickel-10.0 micron Chromium-0.3 micron<br>Salt Spray (500 hrs + Validated)<br>Adhesion (Pass)  |
| <b>Aerator Size</b>                      | WRAS, ACS Approved (20X1)   |
| <b>Available Colour Finishing</b>        | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold Dust (GDS), Full Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)   |

\* As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.