

OPS-WHT-15753P180UFSM+ OPS-WHT-15207

SPECIFICATION DATA SHEET


PRODUCT DETAILS


PRODUCT DETAILS								
Manufacturer :	Jaquar	Туре:	Bowl for coupled closet WC (P trap)					
Range	Opal Outlet Vertical							
Colour:	White	Material:	Ceramic - Vitreous China					
Technical Details:	External diameter of outlet Ø 100 +5 -5 mm	BOM doc.NO.	JSW/01/2018/0107 JSW/01/2018/0159					
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 180 mm							

ARTICLE NAME: COUPLE CLOSET BOWL-WC



TECHNICAL DIMENSIONS





ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP				
Length (mm)	Width (mm)	Height (mm)	eight (mm) Net weight (kg) Rimless WC, UF slim seat cover, Dual Flushing, Anti G					
390	620	825	37.75	Flushing, Comply to Malaysia and Singapore standards				
	ACCESSORIES PROVIDED							
UF Soft Close Seat cover				OPS-WHT-15107UF				
Floor fixing screw				ZPS-SNS-FB02				

CARE AND CLEANING GUIDELINES

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ★ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ★ Carefully inspect the new product for damage before installation.
- ★ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- 🖈 Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- $oldsymbol{\star}$ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1, BS EN 14124:2004, MS 1522:2015/CE All technical dimensions are in accordance to British standards, Bureau of Indian Standards







PACKAGING DETAIL				LOADING PALLET DETAIL			
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	no of pieces on pallet
640	355	420	27.3	1140	1140	2285	16
390	460	215	13.41	1140	1140	2285	60





J _P									
Prepared By		Controlled By		Verified By		Approved B	у		
Designer		Quality control		Product Manager	Manager Sanitaryware		re Head	Head	
Date									
Revision/Version	1	•		Plotter Updated on	Month	22-Aug	Year	2019	